

## **Laboratory Gas Generators**

### TECHNICAL DATA SHEET

## 'LABGAS+' - Intelligent Gas Generators

'LABGAS+', is the latest range of **PSA Laboratory Gas Generators from** Noblegen Products.

Utilising the reliable and efficient PSA technique of separating Nitrogen and Oxygen is used to produce high quality Nitrogen Gas at various flows and purities (see performance data sheets).

The Generators are controlled using the latest in HMI touch screen technology to display the process in real-time, inlet / outlet pressures, Trend graphs and much more......



Features

Range of Flow-rates

air compressor

Auto-run facility Energy saving mode

With or without Internal oil-free

Compact and Quiet design

Outlet flow indicator (% flow)

Trend graphs into MS excel

Alarms with help menu

Audible alarm sounder

Remote access via internt

Purity 99.9995% - 98%

Pharmaceutical & Laboratory:-Gerneral laboratory

GC

ELSD

LC/MS ICP

TurobVap

Hazardous Area Ex Version

**Custom Screens** 

Oxygen analyser

Dew-point sensor

# 17:11:47 22/10/10

**NOBLEGEN** 

model NG1-1 shown

Overview:-

#### New features include:-

Alarm display with help menu

**Outlet Flow Indicator** 

Trend graphs for QA reporting

Energy saving mode

Remote access to Screen using internet

Service alarm and service records page

Oxygen Analyser (optional)

#### NOBLEGEN PRODUCTS

5 PARKER COURT GATESHEAD TYNE & WEAR . **NE11 9EW** 


UNITED KINGDOM

T: +44(0)191 460 1177

F: +44(0)191 460 1079

E: sales@noblegen.co.uk

W: www.noblegen.co.uk



supply of gas is always available. From the process to flow and alarms, including auto-start / stop function, Trend graphs, service alarm and service records page, there is simply no other laboratory nitrogen system quite like LABGAS+.





# Laboratory Gas Generators

## **TECHNICAL DATA SHEET**

## 'LABGAS+' - Intelligent Gas Generators

Nitrogen Outlet Flowrate - NI/min vs Oxygen Concentration									
Model	5ppm	100ppm	0.1%	0.5%	1.0%	2.0%	outlet pressure (barg)	Dims -0	Dims -1
NG1	1.0	-	-	-	-	-	5.0	size 1	size 1
NG3	3.0	-	-	-	-	-	5.0	size 3	size 3
NG4	-	-	3.0	4.0	-	-	5.5	size 1	size 1
NG5	-	4.0	6.0	8.0	10.0	12.0	5.0	size 3	size 3
NG6	-	-	16.0	30.0	35.0	40.0	7.0	size 3	size 3
NG7	-	-	10.0	15.0	20.0	25.0	7.0	size 3	size 3

Specification based on 7barg (102psig) air inlet pressure @ 20°-25°C (68°-77°F) ambient air temperature. For inlet pressures and ambient air temperature outside these conditions please contact Noblegen technical deptartment.

Ambient Temp Range	5-30 °C (41-86 °F)			
Air Inlet Pressure	8 bar g (116 psi g)			
Nitrogen Outlet Pressure*	See table above			
Air Inlet Requirement	Dew-point -40 °C (-40 °F)			
	Particulate: <0.1 micron			
	Oil: <0.01 mg/m <sup>3</sup>			
Electrical Supply	230v a.c. / 1ph / 50-60Hz			
	115v a.c. / 1ph / 50-60Hz			
Socket Inlet	IEC type C14 (fused) 10A max			
Inlet / Outlet Connections	1/4" BSPP			

Dimensions & Weights						
Enclosure size	Height mm	Width mm	Depth mm	Weight Kg		
Size 1	650	320	300	55		
Size 2	650	320	550	65		
Size 3	700	400	660	85		
Size 3 enclosure has castors: add 50mm to height						

Shipping dimensions add 50mm to each above Shipping weight add 17kg to each above



е	а	τ	u	r	е	S

Range of Flow-rates

with or without internal oil-free

air compressor

Compact and quiet design

Purity 99.9995% - 98%

Auto-run facility

Energy saving mode

Outlet flow indicator (% flow)

Trend graphs into MS excel

Alarms with help menu

Audible alarm sounder

Remote access via internet

#### **Applications**

Pharmaceutical

General laboratory

GC

ELSD

LC/MS

ICP

Turbovap

#### Options

Hazardous Area Ex version

Custom screens

Oxygen analyser

Dew-point sensor

#### NOBLEGEN PRODUCTS

5 PARKER COURT GATESHEAD

TYNE & WEAR,

NE11 9EW

UNITED KINGDOM

T: +44(0)191 460 1177

F: +44(0)191 460 1079

E: sales@noblegen.co.uk
W: www.noblegen.co.uk

